


# Custom Series Outdoor Type 2




Scalable outdoor installation LED panel for large-scale signage, entertainment and media applications.



## Key Features

- Choice between Steel or Aluminium Cabinets
- Custom Sizes
- Totally Modular
- Seamless & Bezel-Free
- Front Access

# Custom Series Outdoor Type 2



Product Ref.	DLW-CUS2-FXO-P [X= R/F (Rear/Front) , P= Pitch]			
Pixel Pitch (P)	6mm	8mm	10mm	10mm DIP
LED Type	SMD2727	SMD3535	SMD3535	DIP346 or 570
Module Size	192 x 192mm	320 x 320mm	320 x 320mm	320 x 320mm
Module Resolution (WxH)	32 x 32 dots	40 x 40 dots	32 x 32 dots	32 x 32 dots
Dots Per Modules	1,024 dots	1,600 dots	1,024 dots	1,024 dots
Scan Mode	1/4	1/5	1/2	1/2
Cabinet Size (WxHxD)	960 x 960 x 120mm	960 x 960 x 120mm	960 x 960 x 120mm	960 x 960 x 120mm
Cabinet Resolution (WxH)	160 x 160 dots	120 x 120 dots	96 x 96 dots	96 x 96 dots
Module Quantity (WxH)	5 x 5 = 25pcs	3 x 3 = 9pcs	3 x 3 = 9pcs	3 x 3 = 9pcs
Pixel Density/Cabinet	25,600 dots	14,400 dots	9,216 dots	9,216 dots
Cabinet Material	Steel / Aluminium			
Cabinet Weight	55kg / 40kg			
Max. Brightness	6,000 nits	6,000 nits	6,000 nits	10,000 nits
Viewing Angles (WxH)	160° x 140°	160° x 140°	160° x 140°	160° x 120°
Min. Viewing Distance	≥6m	≥6m	≥10m	≥10m
Gray-Scale	16-bits			
Colors	281 Trillion			
Refresh Rate	1,920Hz / 3,840Hz			
Input Voltage	100-240V / 50-60Hz			
Power Consumption (Max/Ave)	720 / 220W/sqm	650 / 230W/sqm	650 / 230W/sqm	700 / 280W/sqm
MTBF	>10,000Hrs			
Life-Span	≥100,000Hrs			
IP-Rating (Front / Rear)	IP65 / IP54			
Operating Temperatures	40°C to +70°C			
Operating Humidity	10% to 70% RH			
Control System	Colorlight/Novastar-Synchronous/Asynchronous			