


# Portable Series Type 3



Staging production LED panel for flown and stacked applications.





## Key Features

- Standard & Long Cabinet Versions
- Highly Portable
- Mix Splicing Possible
- Strong Corner Protection
- Indoor & Outdoor Versions
- Rear Access
- Pluggable Power Box
- High Refresh Rate
- CE


## Dimensions

2 cabinet sizes available:

500 x 500 x 80mm  
500 x 1000 x 80mm  
(W x H x D)



# Portable Series Type 3



Product Ref.	DLW-PRT3-RRY-P			[Y= I/O (Indoor/Outdoor) , P= Pitch]	
Model Version	Indoor			Outdoor	
Pixel Pitch (P)	2.6mm	2.97mm	3.91mm	3.91mm	4.81mm
LED Type	SMD1515	SMD1515	SMD2121	SMD1921	SMD1921
Module Size	250 x 250 x 15mm			250 x 250 x 15mm	
Module Resolution (WxH)	96 x 96 dots	84 x 84 dots	64 x 64 dots	64 x 64 dots	52 x 52 dots
Dots Per Modules	9,216 dots	7,056 dots	4,096 dots	4,096 dots	2,704 dots
Scan Mode	1/32	1/28	1/16	1/16	1/13
Cabinet Size (WxHxD)	500 x 500 x 80mm		500 x 500 x 80mm / 500 x 1000 x 80mm	500 x 500 x 80mm / 500 x 1000 x 80mm	
Cabinet Resolution (WxH)	192 x 192	168 x 168	128 x 128 / 128 x 256	128 x 128 / 128 x 256	104 x 104 / 104 x 208
Module Quantity (WxH)	2 x 2 pcs	2 x 2 pcs	2 x 2 / 2 x 4pcs	2 x 2 / 2 x 4pcs	
Pixel Density/sqm	147,456 dots	112,896 dots	65,536 dots	65,536 dots	43,264 dots
Cabinet Material	Die-cast Aluminum			Die-cast Aluminum	
Cabinet Weight	6kg	6kg	6kg / 11kg	7kg / 13kg	
Max. Brightness	1,200-1,500 nits			4,500 / 6,500 nits	4,500 nits
Viewing Angles (WxH)	160° x 140°			160° x 140°	
Min. Viewing Distance	≥2.6m	≥3m	≥4m	≥4m	≥5m
Gray-Scale	16-bits			16-bits	
Colors	281 Trillion			281 Trillion	
Refresh Rate	3,840Hz			3,840Hz	
Input Voltage	100-240V / 50-60Hz			100-240V / 50-60Hz	
Power Consumption (Max/Ave)	650 / 200W/sqm	650 / 200W/sqm	600 / 180W/sqm	1,040 / 340W/sqm	1,040 / 340W/sqm
MTBF	>10,000Hrs			>10,000Hrs	
Life-Span	≥100,000Hrs			≥100,000Hrs	
IP-Rating (Front / Rear)	IP45 / IP45			IP65 / IP54	
Operating Temperatures	- 20°C to +45°C			- 20°C to +60°C	
Operating Humidity	0% to 90% RH			0% to 90% RH	
Control System	Colorlight/Novastar -Synchronous			Colorlight/Novastar -Synchronous	